**Product Name: Simplex Fiber Optic Pigtail,** 

Multi-mode, 2mm

\$\circ\$ +989128436521
\$\tilde{\text{\circ}} +987137742628
\$\tilde{\text{\circ}} \text{\circ} \text{\circ}
\$\text{\circ} \text{\circ} \text{\circ} \text{\circ} \text{\circ} \text{\circ} \text{\circ} \text{\circ}
\$\text{\circ} \text{\circ} \

Product Code: SABA-Pig-I-MM-Si-20

## **Features & Applications:**


Simplex pigtails are used for telecom networks and also used for high speed metropolitan and access network.

Applications:

Telecommunication Networks

Local Area Network (LAN)

Connects Between fiber optic patch panel & network Switch



## -Other Details

- SC, LC, ST and FC connectors
- High return loss and low insertion loss
- High reliability and small bend radius
- Good exchangeability
- High tensile strength
- Available in low smoke zero halogen (LSZH) jacket
- Available in different fiber types and lengths
- Conforms to IEC, EIA-TIA performance requirements
- Lifetime Warranty
- Ceramic ferrules
- Guaranteed quality and performance
- 100% tested and recorded for insertion loss and return loss
- RoHS Compliant
- Semi tight buffered easy strip fiber





Electrica	al and mechanical specification							
Item	Data Optic Fiber Pigtail, Multi mode, 2mm							
Product name								
Connector type	SC/ST/FC/LC							
Product type	MM 2mm							
Length	According to request of customer							
Cable jacket type	PVC or LSZH or OFNR or OFNP(on request)							
Fiber Count	Simplex							
Fiber type	OM1, OM2, OM3, OM4							
Insertion Loss	<0.2dB							
Return loss	PC>45 dB , UPC>55 dB , APC>60 dB ≤0.2 dB 1000 times mating cycles							
Repeatability								
Cable Diameter	2 mm							
Jacket Color	Orange, Aqua							
Operating Temperature	-40°C to +85°C							
Standard	IEC 60784-1, IEC 61300, GR-326-CORE, GR-1435, ISO/IEC 11801, AS/NZS ISO/IEC 14763.3, IEC 61280- 4-1, UL 94, ANSI/TIA-598C & RoHS							

ltem	Connector Type	Ferrule Type	Fiber Type		Cable Type		Jacket Material		Cable Color		Cable Diameter		Cable Length	
		/	G.652.D	Single Mode 9/125		16				6	C	10		
	LC ST	UPC	G.657.A1	Single Mode 9/125	sx	Simplex	P	PVC	Y	Yellow	9	0.9mm	01	01 m
			G.657.A2	Single Mode 9/125					0	Orange			1	100
ıgtall			G.655	Single Mode 9/125						-	20	2.0mm	02	02 m
riber Opric rigrail		/	ОМ1	Multi Mode 50/125					W	Orange				
riber		APC	OM2	Multi Mode 50/125	DX	Duplex	L	LSZH	A	Aqua			4	Ü
	FC		ОМЗ	Multi Mode 50/125					В	Blue	30	3.0mm		
5	MU		OM4	Multi Mode 50/125					G	Green			99	99 m

## -Ordering Information