



www.telecomtender.com



نام محصول .

OP کافوی نوری مدل

کد محصول .

FC-ONU-OP

کاربرد و ویژگیها :

ONU صندوق توزیع خطوط مشترکین است که برای ارائه سرویس های voice, data, video و همچنین سرویس های پهن باند و باند باریک استفاده می شود. این دستگاه سیگنال های نوری منتقل شده از طریق فیبر را به سیگنال های الکتریکی تبدیل می کند. همچنین در سیستم های FTTC یا FTTB نیز قابل استفاده می باشد.

- Other Details

- دارای نویز کم و انتخاب آسان سایت
- صرفه جویی در انرژی و سازگار با محیط زیست
- نصب و نگهداری آسان

انواع ظرفیت ها و ابعاد استاندارد محصول بنا به درخواست مشتری موجود می باشد.

- Technical Specification

Uplink Interface

- Gigabit Ethernet Optical, 1000Base-SX, LX, LH, ZX, SFP Module
- Gigabit Ethernet Electrical, 100/1000Base-T Common Units
- CPUM2: Central Process Unit, System

Control and Traffic Uplink

- MGUM: Media Gateway Unit, VoIP Protocol (FL248/MGCP/SIP) Process Unit

Subscriber Line Interface and Units

- POTS, ISDN-BRI, ADSL2/2+, aSHDSL, VDSL2
- RI-POTS2: 48-pod FXS POTS line card
- ATU C2: 48 portADSL/2/2+ line card
- ATU-C2S: 48-pod ADSL/2/2+ line card with built-in splitter
- VTU-C: 24-port VDSL2 tine card
- VTU-CS: 24-port VDSL2 line card with built-in splitter
- STU-C2: 24-port GSM:7SL line card
- IVD: 48-pod POTS+ADSL combined line card

Subscriber Line Card Connection

- 24-port 50-pin RJ-21 connector

Management Interfaces

- t x RS-232 DB-9 console port
- 1 x FE RJ-45 EMS outband management
- 2 x RJ-45 Alarm contacts I/O

Operating conditions: -10 to 60°C(14 to 149° F)

Non-Operating conditions: -19 to 85°C(14 to 185 °F)

Relative Humidity: 5% to 95 %

Storage Humidify: 5% to 95 %

Regulatory Safety Compliance

- EMC: CE: EN550221 class A& EN300386 V1,32
- Safety: EN60950-1
- MTBF: 55,000 hours

MSA Chassis Dimensions (w/d/h)

- 44003400445 mm
- 2 CPU slots, 2 MGU slots, 15 Service Slots
- Weight: -40Kg (Full equipped)

MSB Chassis Dimensions (w/d/h)

- 44003400350 mm
- 2 CPU slots, 2 MGU slots, 8 Service Slots
- Weight: -25Kg (Full equipped)

Power Requirement

DC: -40V - -60V DC

Power Consumption

- MSA: <900 Watts (Full equipped)
- MSB: <600 Watts (Full equipped)